

Ultra ONE[®] Wheel with MagnaForce[®] Alloy

22.5 x 9.00, 10-285



Less Weight, Better Fuel Economy and More Payload.

We've upped the ante. Alcoa[®] Ultra ONE[®] 22.5" x 9" Wheels utilise proprietary MagnaForce[®] alloy to save you more than 23kg. versus a comparable steel wheel for improved productivity without sacrificing load rating.

Tough Jobs Demand Tough Wheels.

Waste collection, logging, mining and other heavy duty applications demand a tough wheel. These wheels are built for your toughest jobs.

A True Lightweight Heavyweight.

Each wheel offers a 4535KG load rating. Yet at just 22 or 25 KG's, based on fitment, these wheels are the lightest in the market.

Additional Benefits


- One piece forged strength that's 5x stronger than steel.
- No painting. Lower maintenance costs.
- True cool running extends tyre and brake life.
- Same five year limited warranty you've come to expect



89U63X



89U64X



Improved Security

Increased aluminium wheel mounting thickness for improved fastener torque retention, providing maximum grip length



DRIVING YOUR **BOTTOM LINE**[™]



Ultra ONE[®] Wheel with MagnaForce[®] Alloy

22.5 x 9.00, 10-285



Wheel Specifications

Alcoa[®] aluminium disc wheel mounting dimensions are consistent with SAE Recommended Practice J694 June 2007.

22.5 x 9 – ISO Metric Hub Piloted Mount, 10 x 26mm Bolt Hole – 285.75mm Bolt Circle, 220.1mm Hub Bore							
Part Number	Est Weight KG	X=Finish Options	OFFSET Outset mm	OFFSET Inset mm	Max Load KG	Max inflation PSI	Valve Stem
89U63X*	22	1,7 0DB, 1DB, 2DB	102.62	79.25	4535	130	TR555E
89U64X	25.4	1,2,3,7, 0DB,1DB, 2DB,3DB	176.28	152.40	4535	130	TR554D



* 0 and 7 finish options on certain wheels are determined by inset or outset mounting positions and may not be finished on both sides. See chart for position and available finish options

SURFACE OPTION CODES COMPLETE LISTING

- | | |
|--|---|
| 0 Brush Finish on both sides as applicable | 7 LvL ONE™ Finish on both sides as applicable |
| 1 Polished Outside Only | 8 LvL ONE™ Finish on both sides. |
| 2 Polished Inside Only | 9 Brush Finish on both sides. |
| 3 Polished Both Sides | |
| DB Dura-Bright [®] Surface Treatment | DD Dura-Bright [®] and Dura-Flange [®] Wear Protection |
| DF Dura-Flange [®] Wear Protection | |



www.alcoawheels.com.au



HOWMET WHEEL SYSTEMS AUSTRALIA PTY LTD
 1800 955 191 | 18 Law Court, Sunshine West, Victoria 3020
www.alcoawheels.com.au

