Cleaning Alcoa® Wheels




Cleaning Dura-Bright® Wheels





1.



Allow wheels to cool below 35° C Remove nut covers. 2.



Rinse with water.

3.



Mix water with a mild detergent or use undiluted Dura-Bright® Wheel Wash.

4.



Clean the wheel with a soft brush.

5.



Rinse with water.



Before



After

Watch the video instructions





youtu.be/QU9ggcm8Hhl Or look for "How to clean Dura-Bright® Alcoa Wheels"

Dura-Bright® Wheel Wash

- Helps to prevent the build-up of brake dust resin and copper glow
- No risk of damaging wheels with harsh chemicals
- No need to dilute
- Suitable for both XBR® and EVO technology



Cleaning Alcoa® Wheels



LvL ONE®, Polished and Brushed wheels





1.



Rinse with warm water; preferably with a high pressure cleaner.

2.



Pour a quantity of ALclean into a bucket and dilute with 1, 2 or 3 parts of water.

3.



Recommended quantities:

- 1. for difficult spots
- 2. for medium pollution
- 3. for regular use
- 4. for frequent use

4



Gently brush ALclean onto the wheel.

5.



Rinse with clean water. Repeat these steps if needed.

6.



Dry the wheel.

LvL ONE® and Polished wheels

7.



Continue by applying a small amount of Alpolish.

8



Spread it evenly over the wheel using a moist cloth and polish the wheel.

0



Repeat steps 7 and 8 section by section to prevent the polish from drying out

Alcoa® Wheels cleaning products

ALclean

- Removes oxidation, disk brake dust, salt spray and general stains
- Suitable for Brushed, LvL ONE® and Mirror Polished finishes

ALpolish

- Restores shine of Mirror Polished and LvL ONE® finishes
- Use after ALclean

ALbrush2

- Rubber edge to avoid damage of the wheel
- 6 cm polyester plucked fibres



For additional information on cleaning and maintenance see page 84 of the Service Manual for Alcoa Wheels.