



Alcoa Wheel Accessories 2019

Please contact us by this free dial if you have any question.



0120-39-1416

Cleaner

Super Shine Aluminum Polish is polished agent for daily maintenance for Alcoa forged wheel and degraded polish surface. It is possible to remove slight scratch . Heavy Duty Aluminum Wash is high acid agent and it is for removing thin oxide surface, refractory stain.
 ※ After using Aluminum Wash, Aluminum Polish care is necessary.
 ※ These are not used for Dura Bright and other coated wheel.



| Part No. | item | Content | Unit |
|----------|-----------------------------|---------|------------|
| 44016 | Super Shine Aluminum Polish | 473ml | 12 bottles |
| 15016 | Heavy Beauty Aluminum Wash | 473ml | 12 bottles |

Disk Mate

Disk Mate should be mounted between Hub and wheel in order to protect defect, dust, rust. In addition, it is useful for wear of Hub/Wheel, noise from wheel contact area.
 *It is available for Alcoa forged aluminum wheel only.



| Part No. | Hb(mm) | Bolt Hole(mm) | Item | | | Unit |
|----------|--------|---------------|-------------------|------|-----------|--------|
| 013000 | 335 | 30 | 22.5 inch | 10 H | ISO wheel | 10 pcs |
| 014000 | 225 | 30 | 19.5 inch | 8 H | ISO wheel | 10 pcs |
| 023000 | 221 | 40 | 22.5 inch | 8 H | JIS wheel | 10 pcs |
| 0240001 | 165 | 25 | 16/17.5/19.5 inch | 6 H | JIS wheel | 10 pcs |

Sleeve Nut/Insert

The sleeve nut is for Arconic original nut for bolt hole diameter 32mm wheel, that are available wheel 766413, 878513 886513, 896513.there is two types screw threads for Metric and BSF. Sleeve goes into 32mm bolt hole and it is possible to mount Alcoa wheel without replacement for steel wheel stud bolt.



| Part No. | Item | | remark | |
|----------|-----------------------------|-------------|---------------------------|------------------------------|
| 5780.32 | M22-1.5 | Right screw | Single | Metric screw thread for Benz |
| 5781.32 | M22-1.5 | Right screw | Double | Metric screw thread for Benz |
| 5784.32 | 7/8"-11 BSF | Right screw | Single | BSF screw thread for Scania |
| 5785.32 | 7/8"-11 BSF | Right screw | Double | BSF screw thread for Scania |
| 5000.00 | Insert with Alcoa logo mark | | Attachment for sleeve nut | |

※The insert is involved in above sleeve when you purchase. Purchasing insert only is available.

※Above picture is different from ARMS nut.

Grease

FreyLube is water isolated grease. Please apply this grease at O-ring and grommet air valve as a proper quantity. It is useful for prevention for sticking wheel on hub by anti-freezing agent.
 ※Don't stick on hub and a contact surface to hub.



| Part No. | Item | Content | Unit |
|----------|----------|---------|--------|
| FL2000 | FleyLube | 2kg | 1 case |

Air Valve

When you place order the valve, please check part number of wheel or valve part number.

※Arconic recommend to replace new valve once a year.



| ValvePartNo. | WheelPartNo. | | | | | | | | |
|--------------|--------------|-------------|----------|----------|----------|-------------|--------|--------|--|
| TR543CN | 250003 | 251003 | 260003 | 353013 | 353023 | | | | |
| TR543C | 663113 | 663123 | 663133 | 663713 | 663733 | 763323 | 763353 | 764713 | |
| TR544C | 653013 | 653023 | 663013 | 663823 | 873353 | 883353 | | | |
| TR544D | 663103 | 810520 | 813540 | 813542 | 841542 | 873323 | 873343 | 883323 | |
| TR542 | 813540 | 813542 | | | | | | | |
| TR543D | 663203 | | | | | | | | |
| 60MS27N | 874503 | 884553 | 884563 | 884573 | 885553 | 886503 | 894533 | 894553 | |
| | 894573 | 895553 | | | | | | | |
| 70MS7SE | 763423 | 871523 | 874523 | 881523 | 886513 | 886523 | 886533 | 896513 | |
| | 896523 | 896533 | | | | | | | |
| 70MS7SL | 878513 | 882523DB *1 | | | | | | | |
| 70MS7 | 768423 | 768423DB | 871523DB | 874523DB | 881523DB | 882523DB *1 | | | |

*1: 70MS7SL and 70MS7 both are adoptable for 882523DB.



Arconic Japan Ltd.
 1013 Hibiya U-1 Bldg. 1-1-7 Uchisaiwaicho
 Tokyo, Japan 100-0011
 TEL : 03-3539-6630 FAX : 03-3539-6637