

## Maximum Performance. Built for Tough Jobs.

All the light weight strength and durability you've come to expect from the leader in heavy duty forged aluminum wheels, engineered for your truck .



Alcoa<sup>®</sup> Forged Aluminum Wheels

# Navistar CV & Chevrolet Silverado 4500/5500/6500

Follow Us: f 🗈 🖸 in

# Alcoa® Forged Aluminum Wheels Navistar CV & Chevrolet Silverado 4500/5500/6500



## Spec Dura-Bright<sup>®</sup> Wheels for the easiest-to-clean wheels ever.

Dura-Bright<sup>®</sup> surface treatment penetrates the aluminum, forming a molecular bond that becomes part of the wheel itself. That means it won't crack, peel or corrode like coated wheels, looking newer for longer.

#### Dura-Bright<sup>®</sup>



#### **Conventional Coating**

WHEEL SPECIFICATIONS







### Look Good

- Never rusts
- Sleek design for premium appearance
- Eliminate the need for simulators

#### **Get Stronger**

 Aluminum wheels are 5x stronger than steel

### **Drive Smarter**

- Run cooler to increase brake and tire life & performance
- Backed by a 5-year warranty
- High resale value

### **Lighter is Better**

- Save 125 lbs converting to aluminum
- More payload
- Increase fuel economy

#### **Less Maintenance**

- Does not require painting
- Save time & money

# SAE Recommended Practice J694 June 2007. Vehicle applications are subject to model year changes. Prior to mounting tires perform a wheel fitment check to ensure clearance from any obstructions.

Alcoa® aluminum disc wheel mounting dimensions are consistent with

	Size (in)	P/N	Weight (lbs)	Finish Options	SURFACE TREATMENTS	MOUNTING SYSTEM				OFFSET		LOAD RATING	
					Dura- Bright®	Bolt Holes	Bolt Circle	Bolt Hole Dia.	Hub Bore	Outset	Inset	Max Load (lbs)	Max Cold Infl. (psi)
Hub Pilot	19.5 x 6.75	76543x	27	1, 2, 7	1DB, 2DB	8	275mm	26mm	8.7″	5.8″	5.1″	4190	120

#### OPTIONAL WHEEL ACCESSORIES MOUNTING SYSTEM

Offered as kits or individual components, these accessories complement aluminum wheel design and fit directly over OE hardware.

Application: Screw on nut covers to secure cap; requires a minimum of 3 threads required. Black spacer not applicable with short lug nut. Center cap removes for access to hub.

Part Number		Description					Bolt Circle		
008221	Fro	nt hub cover kit	for 33mm he	x flange nut	is.	8 x 275m	m		
008222	Rea	ar hub cover kit f	for 33mm he	x flange nut	s.	8 x 275m	m		
082122	Front	hub cover kit (ax	le) for 33mm	hex flange	nuts.	8 x 275m	m		
082133	Rear h	ub cover kits (ax	le) for 33mm	hex flange	nuts.	8 x 275m	m		

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. More information regarding CA Prop 6S warning(s) available on our website: www.alcoawheels.com



© 2023 Howmet Aerospace Inc. The Alcoa trademarks are owned by Alcoa USA Corporation and used by Howmet Aerospace Inc. and its subsidiaries under license from Alcoa USA Corporation.