



Maximum Performance. Built for Sprinter 3500.

We have taken all of our light weight strength and durability from heavy duty forged aluminum wheels and reinvented it specifically for the Sprinter 3500.



Alcoa® Wheels for Sprinter Vehicles 16" x 5.5J" Wheels

25180x

Follow Us:



Alcoa® Wheels For Sprinter Vehicles

25180x



Get the finest durability, quality, and style combined with advanced finishes for your Sprinter vehicle today!



Lower lifetime vehicle operating costs



Reduce wheel maintenance



Lower fuel expenses



Reduce costs from curbing



Aluminum is the green solution. Add all of the benefits up to lower your operating and maintenance costs.



OPTIONAL ACCESSORIES

Offered as kits or individual components, these accessories complement aluminum wheel design and fit directly over OE hardware.



021135



000135



022135

PART NUMBER	DESCRIPTION	SOLD AS
000135	Single Lug Nut Cover	EACH
021135	Front Hub Cover Kit Includes 2 front hub covers and 12 lug nut covers	Kit
022135	Rear Hub Cover Kit Includes 2 rear hub covers and 12 lug nut covers	Kit

WHEEL SPECIFICATIONS

Alcoa® aluminum disc wheel mounting dimensions are consistent with SAE Recommended Practice J694 May 2015 or ISO 4107:2010 where applicable. Vehicle applications are subject to model year changes. Prior to mounting tires perform a wheel fitment check to ensure clearance from any obstructions.

	Size (in)	P/N	Weight (lbs)	Finish Options	SURFACE TREATMENTS	MOUNTING SYSTEM				OFFSET		LOAD RATING		Valve Stem
					Dura-Bright®	Bolt Holes	Bolt Circle	Bolt Hole Dia.	Hub Bore	Outset	Inset	Max Load (lbs)	Max Cold Infl. (psi)	
Hub Pilot	16 x 5.5J	25180x	16	0	1DB, 2DB	6	205mm	16mm	161.1mm	125.5mm	116.3mm	2340	80	54MS00



TAKE A LOOK AT THE COMPLETE ALCOA® WHEELS SPEC GUIDE.

FINISH OPTIONS

- 1 Mirror Polish – steer/outside only
 - 2 Mirror Polish – inside only
 - 3 Mirror Polish – both sides
 - 7 High Polish – both sides as applicable
 - 8 High Polish – both sides as applicable
- Reference data table for offset position

SURFACE TREATMENTS

- DB** Dura-Bright® Surface Treatment
- DF** Dura-Flange® Wear Protection
- DD** Dura-Bright® and Dura-Flange® Wear Protection
- BLK** Dura-Black™ Surface Treatment

° 0 and 7 finish options are determined by inset or outset mounting positions and may not be finished on both sides. See chart for position and available finish options.



1616 Harvard Ave. Cleveland, OH 44105

1-800-242-9898

www.alcoawheels.com



© 2023 Howmet Aerospace Inc. The Alcoa trademarks are owned by Alcoa USA Corporation and used by Howmet Aerospace Inc. and its subsidiaries under license from Alcoa USA Corporation.