



# Engineered to expand our 22.5"x 8.25" portfolio



**Alcoa® 88167x**  
**22.5" x 8.25" Wheel**



Best-In-Class  
Warranty



Increase Fuel  
Efficiency



Look  
Great



Quick ROI



# Alcoa® 88167x

## 22.5" x 8.25" Wheel

Alcoa® Wheels integrates their proprietary MagnaForce® alloy and vHub™ Bore Technology into the 88167x wheel design. This wheel represents our expertise in advanced innovation, manufacturing, and engineering for the road. Ideal for heavy-duty truck, trailer, and motorhome applications. This wheel family comes with four Dura-Bright® options to choose from.



### HUB PILOT – 10 BOLT HOLES, 285.75MM BOLT CIRCLE, 220.1MM BORE

Alcoa® aluminum disc wheel mounting dimensions are consistent with SAE Recommended Practice J694.

Size (in)	P/N	Weight (lbs)	Finish Options	SURFACE TREATMENT OPTIONS				Bolt Hole Dia.	OFFSET		LOAD RATING		Valve Stem
				Dura-Black™	Dura-Bright®	Dura-Flange®	Dura-Bright® Dura-Flange®		Outset (in)	Inset (in)	Max Load (lbs)	Max Cold Infl. (psi)	
22.5" x 8.25"	88167x	39	1, 2, 3, 7	BLK	0DB, 1DB, 2DB, 3DB			26mm	6.6	5.81	7,400	130	TV554D (Non-TPMS)



**TAKE A LOOK AT THE COMPLETE ALCOA® WHEELS SPEC GUIDE.**

#### FINISH OPTIONS DESCRIPTIONS

- 1 Mirror Polish – steer/outside only
  - 2 Mirror Polish – inside only
  - 3 Mirror Polish – both sides
  - 7 High Polish – both sides as applicable
  - 8 High Polish – both sides as applicable
- Reference data table for offset position

#### SURFACE TREATMENTS

- DB** Dura-Bright® Surface Treatment
- DF** Dura-Flange® Wear Protection
- DD** Dura-Bright® and Dura-Flange® Wear Protection
- BLK** Dura-Black™ Surface Treatment

° 0 and 7 finish options are determined by inset or outset mounting positions and may not be finished on both sides. See chart for position and available finish options.

12/24